

AMENDATORY SECTION (Amending Order 03-10, filed 11/30/04, effective 1/1/05)

WAC 173-303-040 Definitions. When used in this chapter, the following terms have the meanings given below.

"Aboveground tank" means a device meeting the definition of "tank" in this section and that is situated in such a way that the entire surface area of the tank is completely above the plane of the adjacent surrounding surface and the entire surface area of the tank (including the tank bottom) is able to be visually inspected.

"Active life" of a facility means the period from the initial receipt of dangerous waste at the facility until the department receives certification of final closure.

"Active portion" means that portion of a facility which is not a closed portion, and where dangerous waste recycling, reuse, reclamation, transfer, treatment, storage or disposal operations are being or have been conducted after:

The effective date of the waste's designation by 40 CFR Part 261; and

March 10, 1982, for wastes designated only by this chapter and not designated by 40 CFR Part 261. (See also "closed portion" and "inactive portion.")

"Active range" means a military range that is currently in service and is being regularly used for range activities.

"Acute hazardous waste" means dangerous waste sources (listed in WAC 173-303-9904) F020, F021, F022, F023, F026, or F027, and discarded chemical products (listed in WAC 173-303-9903) that are identified with a dangerous waste number beginning with a "P", including those wastes mixed with source, special nuclear, or by-product material subject to the Atomic Energy Act of 1954. The abbreviation "AHW" will be used in this chapter to refer to those dangerous and mixed wastes which are acute hazardous wastes. Note - the terms acute and acutely are used interchangeably.

"Ancillary equipment" means any device including, but not limited to, such devices as piping, fittings, flanges, valves, and pumps, that is used to distribute, meter, or control the flow of dangerous waste from its point of generation to a storage or treatment tank(s), between dangerous waste storage and treatment tanks to a point of disposal on-site, or to a point of shipment for disposal off-site.

"Aquifer" means a geologic formation, group of formations, or part of a formation capable of yielding a significant amount of ground water to wells or springs.

"Batch" means any waste which is generated less frequently than once a month.

"Battery" means a device consisting of one or more electrically connected electrochemical cells which is designed to

receive, store, and deliver electric energy. An electrochemical cell is a system consisting of an anode, cathode, and an electrolyte, plus such connections (electrical and mechanical) as may be needed to allow the cell to deliver or receive electrical energy. The term battery also includes an intact, unbroken battery from which the electrolyte has been removed.

"Berm" means the shoulder of a dike.

"Boiler" means an enclosed device using controlled flame combustion and having the following characteristics:

The unit must have physical provisions for recovering and exporting thermal energy in the form of steam, heated fluids, or heated gases; and

The unit's combustion chamber and primary energy recovery section(s) must be of integral design. To be of integral design, the combustion chamber and the primary energy recovery section(s) (such as waterwalls and superheaters) must be physically formed into one manufactured or assembled unit. A unit in which the combustion chamber and the primary energy recovery section(s) are joined only by ducts or connections carrying flue gas is not integrally designed; however, secondary energy recovery equipment (such as economizers or air preheaters) need not be physically formed into the same unit as the combustion chamber and the primary energy recovery section. The following units are not precluded from being boilers solely because they are not of integral design: Process heaters (units that transfer energy directly to a process stream), and fluidized bed combustion units; and

While in operation, the unit must maintain a thermal energy recovery efficiency of at least sixty percent, calculated in terms of the recovered energy compared with the thermal value of the fuel; and

The unit must export and utilize at least seventy-five percent of the recovered energy, calculated on an annual basis. In this calculation, no credit will be given for recovered heat used internally in the same unit. (Examples of internal use are the preheating of fuel or combustion air, and the driving of induced or forced draft fans or feedwater pumps); or

The unit is one which the department has determined, on a case-by-case basis, to be a boiler, after considering the standards in WAC 173-303-017(6).

"By-product" means a material that is not one of the primary products of a production process and is not solely or separately produced by the production process. Examples are process residues such as slags or distillation column bottoms. The term does not include a coproduct that is produced for the general public's use and is ordinarily used in the form it is produced by the process.

"Carbon regeneration unit" means any enclosed thermal treatment device used to regenerate spent activated carbon.

"Carcinogenic" means a material known to contain a substance which has sufficient or limited evidence as a human or animal carcinogen as listed in both IARC and either IRIS or HEAST.

"Cathode ray tube" or "CRT" means a vacuum tube, composed primarily of glass, which is the visual or video display component

of an electronic device. A used, intact CRT means a CRT whose vacuum has not been released. A used, broken CRT means glass removed from its housing or casing whose vacuum has been released.

"Chemical agents and chemical munitions" are defined as in 50 U.S.C. section 1521 (j) (1).

"Cleanup-only facility" means a site, including any contiguous property owned or under the control of the owner or operator of the site, where the owner or operator is or will be treating, storing, or disposing of remediation waste, including dangerous remediation waste, and is not, has not and will not be treating, storing or disposing of dangerous waste that is not remediation waste. A cleanup-only facility is not a "facility" for purposes of corrective action under WAC 173-303-646.

"Closed portion" means that portion of a facility which an owner or operator has closed, in accordance with the approved facility closure plan and all applicable closure requirements.

"Closure" means the requirements placed upon all TSD facilities to ensure that all such facilities are closed in an acceptable manner (see also "post-closure").

"Commercial chemical product or manufacturing chemical intermediate" refers to a chemical substance which is manufactured or formulated for commercial or manufacturing use which consists of the commercially pure grade of the chemical, any technical grades of the chemical that are produced or marketed, and all formulations in which the chemical is the sole active ingredient.

"Commercial fertilizer" means any substance containing one or more recognized plant nutrients and which is used for its plant nutrient content and/or which is designated for use or claimed to have value in promoting plant growth, and includes, but is not limited to, limes, gypsum, and manipulated animal manures and vegetable compost. The commercial fertilizer must be registered with the state or local agency regulating the fertilizer in the locale in which the fertilizer is being sold or applied.

"Compliance procedure" means any proceedings instituted pursuant to the Hazardous Waste Management Act as amended in 1980 and 1983, and chapter 70.105A RCW, or regulations issued under authority of state law, which seeks to require compliance, or which is in the nature of an enforcement action or an action to cure a violation. A compliance procedure includes a notice of intention to terminate a permit pursuant to WAC 173-303-830(5), or an application in the state superior court for appropriate relief under the Hazardous Waste Management Act. A compliance procedure is considered to be pending from the time a notice of violation or of intent to terminate a permit is issued or judicial proceedings are begun, until the department notifies the owner or operator in writing that the violation has been corrected or that the procedure has been withdrawn or discontinued.

"Component" means either the tank or ancillary equipment of a tank system.

"Constituent" or "dangerous waste constituent" means a chemically distinct component of a dangerous waste stream or mixture.

"Container" means any portable device in which a material is stored, transported, treated, disposed of, or otherwise handled.

"Containment building" means a hazardous waste management unit that is used to store or treat hazardous waste under the provisions of WAC 173-303-695.

"Contingency plan" means a document setting out an organized, planned, and coordinated course of action to be followed in case of a fire, explosion, or release of dangerous waste or dangerous waste constituents which could threaten human health or environment.

"Contract" means the written agreement signed by the department and the state operator.

"Corrosion expert" means a person who, by reason of his knowledge of the physical sciences and the principles of engineering and mathematics, acquired by a professional education and related practical experience, is qualified to engage in the practice of corrosion control on buried or submerged metal piping systems and metal tanks. Such a person must be certified as being qualified by the National Association of Corrosion Engineers (NACE) or be a registered professional engineer who has certification or licensing that includes education and experience in corrosion control on buried or submerged metal piping systems and metal tanks.

"CRT collector" means a person who receives CRTs for recycling, repair, resale, or donation.

"CRT glass manufacturer" means an operation or part of an operation that uses a furnace to manufacture CRT glass.

"CRT processing" means conducting all of the following activities:

- Receiving broken or intact CRTs; and
- Intentionally breaking intact CRTs or further breaking or separating broken CRTs; and
- Sorting or otherwise managing glass removed from CRT monitors.

"Dangerous waste constituents" means those constituents listed in WAC 173-303-9905 and any other constituents that have caused a waste to be a dangerous waste under this chapter.

"Dangerous waste management unit" is a contiguous area of land on or in which dangerous waste is placed, or the largest area in which there is a significant likelihood of mixing dangerous waste constituents in the same area. Examples of dangerous waste management units include a surface impoundment, a waste pile, a land treatment area, a landfill cell, an incinerator, a tank and its associated piping and underlying containment system and a container storage area. A container alone does not constitute a unit; the unit includes containers and the land or pad upon which they are placed.

"Dangerous wastes" means those solid wastes designated in WAC 173-303-070 through 173-303-100 as dangerous, or extremely hazardous or mixed waste. As used in this chapter, the words "dangerous waste" will refer to the full universe of wastes regulated by this chapter. The abbreviation "DW" will refer only to that part of the regulated universe which is not extremely

hazardous waste. (See also "extremely hazardous waste," "hazardous waste," and "mixed waste" definitions.)

"Debris" means solid material exceeding a 60 mm particle size that is intended for disposal and that is: A manufactured object; or plant or animal matter; or natural geologic material. However, the following materials are not debris: Any material for which a specific treatment standard is provided in 40 CFR Part 268 Subpart D (incorporated by reference in WAC 173-303-140 (2)(a)); process residuals such as smelter slag and residues from the treatment of waste, wastewater, sludges, or air emission residues; and intact containers of hazardous waste that are not ruptured and that retain at least seventy-five percent of their original volume. A mixture of debris that has not been treated to the standards provided by 40 CFR 268.45 and other material is subject to regulation as debris if the mixture is comprised primarily of debris, by volume, based on visual inspection.

"Department" means the department of ecology.

"Dermal LD₅₀" means the single dosage in milligrams per kilogram (mg/kg) body weight which, when dermally (skin) applied for 24 hours, within 14 days kills half of a group of ten rabbits each weighing between 2.0 and 3.0 kilograms.

"Designated facility" means a dangerous waste treatment, storage, or disposal facility that has received a permit (or interim status) in accordance with the requirements of this chapter, has received a permit (or interim status) from another state authorized in accordance with 40 CFR Part 271, has received a permit (or interim status) from EPA in accordance with 40 CFR Part 270, has a permit by rule under WAC 173-303-802(5), or is regulated under WAC 173-303-120 (4)(c) or 173-303-525 when the dangerous waste is to be recycled, and that has been designated on the manifest pursuant to WAC 173-303-180(1). If a waste is destined to a facility in an authorized state that has not yet obtained authorization to regulate that particular waste as dangerous, then the designated facility must be a facility allowed by the receiving state to accept such waste. The following are designated facilities only for receipt of state-only waste; they cannot receive federal hazardous waste from off-site: Facilities operating under WAC 173-303-500 (2)(c).

"Designation" is the process of determining whether a waste is regulated under the dangerous waste lists, WAC 173-303-080 through 173-303-082; or characteristics, WAC 173-303-090; or criteria, WAC 173-303-100. The procedures for designating wastes are in WAC 173-303-070. A waste that has been designated as a dangerous waste may be either DW or EHW.

"Destination facility" means a facility that treats, disposes of, or recycles a particular category of universal waste, except those management activities described in WAC 173-303-573 (9)(a), (b) and (c) and 173-303-573 (20)(a), (b) and (c). A facility at which a particular category of universal waste is only accumulated, is not a destination facility for purposes of managing that category of universal waste.

"Dike" means an embankment or ridge of natural or man-made

materials used to prevent the movement of liquids, sludges, solids, or other substances.

"*Dioxins and furans (D/F)*" means tetra, penta, hexa, hepta, and octa-chlorinated dibenzo dioxins and furans.

"Director" means the director of the department of ecology or his designee.

"Discharge" or "dangerous waste discharge" means the accidental or intentional release of hazardous substances, dangerous waste or dangerous waste constituents such that the substance, waste or a waste constituent may enter or be emitted into the environment.

"Disposal" means the discharging, discarding, or abandoning of dangerous wastes or the treatment, decontamination, or recycling of such wastes once they have been discarded or abandoned. This includes the discharge of any dangerous wastes into or on any land, air, or water.

"Domestic sewage" means untreated sanitary wastes that pass through a sewer system to a publicly owned treatment works (POTW) for treatment.

"Draft permit" means a document prepared under WAC 173-303-840 indicating the department's tentative decision to issue or deny, modify, revoke and reissue, or terminate a permit. A notice of intent to terminate or deny a permit are types of draft permits. A denial of a request for modification, revocation and reissuance, or termination as discussed in WAC 173-303-830 is not a draft permit.

"Drip pad" is an engineered structure consisting of a curbed, free-draining base, constructed of nonearthen materials and designed to convey preservative kick-back or drippage from treated wood, precipitation, and surface water run-on to an associated collection system at wood preserving plants.

"Elementary neutralization unit" means a device which:

Is used for neutralizing wastes which are dangerous wastes only because they exhibit the corrosivity characteristics defined in WAC 173-303-090 or are listed in WAC 173-303-081, or in 173-303-082 only for this reason; and

Meets the definition of tank, tank system, container, transport vehicle, or vessel.

"Enforceable document" means an order, consent decree, plan or other document that meets the requirements of 40 CFR 271.16(e) and is issued by the director to apply alternative requirements for closure, post-closure, ground water monitoring, corrective action or financial assurance under WAC 173-303-610 (1)(d), 173-303-645 (1)(e), or 173-303-620 (8)(d) or, as incorporated by reference at WAC 173-303-400, 40 CFR 265.90(f), 265.110(d), or 265.140(d). Enforceable documents include, but are not limited to, closure plans and post-closure plans, permits issued under chapter 70.105 RCW, orders issued under chapter 70.105 RCW and orders and consent decrees issued under chapter 70.105D RCW.

"Environment" means any air, land, water, or ground water.

"EPA/state identification number" or "EPA/state ID#" means the number assigned by EPA or by the department of ecology to each

generator, transporter, and TSD facility.

"Existing tank system" or "existing component" means a tank system or component that is used for the storage or treatment of dangerous waste and that is in operation, or for which installation has commenced on or prior to February 3, 1989. Installation will be considered to have commenced if the owner or operator has obtained all federal, state, and local approvals or permits necessary to begin physical construction of the site or installation of the tank system and if either:

A continuous on-site physical construction or installation program has begun; or

The owner or operator has entered into contractual obligations, which cannot be canceled or modified without substantial loss, for physical construction of the site or installation of the tank system to be completed within a reasonable time.

"Excluded scrap metal" is processed scrap metal, unprocessed home scrap metal, and unprocessed prompt scrap metal.

"Existing TSD facility" means a facility which was in operation or for which construction commenced on or before November 19, 1980, for wastes designated by 40 CFR Part 261, or August 9, 1982, for wastes designated only by this chapter and not designated by 40 CFR Part 261. A facility has commenced construction if the owner or operator has obtained permits and approvals necessary under federal, state, and local statutes, regulations, and ordinances and either:

A continuous on-site, physical construction program has begun; or

The owner or operator has entered into contractual obligation, which cannot be (~~cancelled~~) canceled or modified without substantial loss, for physical construction of the facility to be completed within a reasonable time.

"Explosives or munitions emergency" means a situation involving the suspected or detected presence of unexploded ordnance (UXO), damaged or deteriorated explosives or munitions, an improvised explosive device (IED), other potentially explosive material or device, or other potentially harmful military chemical munitions or device, that creates an actual or potential imminent threat to human health, including safety, or the environment, including property, as determined by an explosives or munitions emergency response specialist. Such situations may require immediate and expeditious action by an explosives or munitions emergency response specialist to control, mitigate, or eliminate the threat.

"Explosives or munitions emergency response" means all immediate response activities by an explosives and munitions emergency response specialist to control, mitigate, or eliminate the actual or potential threat encountered during an explosives or munitions emergency. An explosives or munitions emergency response may include in-place render-safe procedures, treatment or destruction of the explosives or munitions and/or transporting those items to another location to be rendered safe, treated, or

destroyed. Any reasonable delay in the completion of an explosives or munitions emergency response caused by a necessary, unforeseen, or uncontrollable circumstance will not terminate the explosives or munitions emergency. Explosives and munitions emergency responses can occur on either public or private lands and are not limited to responses at RCRA facilities.

"Explosives or munitions emergency response specialist" means an individual trained in chemical or conventional munitions or explosives handling, transportation, render-safe procedures, or destruction techniques. Explosives or munitions emergency response specialists include Department of Defense (DOD) emergency explosive ordnance disposal (EOD), technical escort unit (TEU), and DOD-certified civilian or contractor personnel; and other federal, state, or local government, or civilian personnel similarly trained in explosives or munitions emergency responses.

"Extremely hazardous waste" means those dangerous and mixed wastes designated in WAC 173-303-100 as extremely hazardous. The abbreviation "EHW" will be used in this chapter to refer to those dangerous and mixed wastes which are extremely hazardous. (See also "dangerous waste" and "hazardous waste" definitions.)

"Facility" means:

- All contiguous land, and structures, other appurtenances, and improvements on the land used for recycling, reusing, reclaiming, transferring, storing, treating, or disposing of dangerous waste. A facility may consist of several treatment, storage, or disposal operational units (for example, one or more landfills, surface impoundments, or combination of them). Unless otherwise specified in this chapter, the terms "facility," "treatment, storage, disposal facility," "TSD facility," "dangerous waste facility" or "waste management facility" are used interchangeably.

- For purposes of implementing corrective action under WAC 173-303-64620 or 173-303-64630, "facility" also means all contiguous property under the control of an owner or operator seeking a permit under chapter 70.105 RCW or chapter 173-303 WAC and includes the definition of facility at RCW 70.105D.020(4).

"Facility mailing list" means the mailing list for a facility maintained by the department in accordance with WAC 173-303-840 (3) (e) (I) (D).

"Final closure" means the closure of all dangerous waste management units at the facility in accordance with all applicable closure requirements so that dangerous waste management activities under WAC 173-303-400 and 173-303-600 through 173-303-670 are no longer conducted at the facility. Areas only subject to generator standards WAC 173-303-170 through 173-303-230 need not be included in final closure.

"Fish LC50" means the concentration that will kill fifty percent of the exposed fish in a specified time period. For book designation, LC50 data must be derived from an exposure period greater than or equal to twenty-four hours. A hierarchy of species LC50 data should be used that includes (in decreasing order of preference) salmonids, fathead minnows (*Pimephales promelas*), and

other fish species. For the ninety-six-hour static acute fish toxicity test, described in WAC 173-303-110 (3)(b)(i), coho salmon (*Oncorhynchus kisutch*), rainbow trout (*Oncorhynchus mykiss*), or brook trout (*Salvelinus fontinalis*) must be used.

"Food chain crops" means tobacco, crops grown for human consumption, and crops grown to feed animals whose products are consumed by humans.

"Freeboard" means the vertical distance between the top of a tank or surface impoundment dike, and the surface of the waste contained therein.

"Fugitive emissions" means the emission of contaminants from sources other than the control system exit point. Material handling, storage piles, doors, windows and vents are typical sources of fugitive emissions.

"Generator" means any person, by site, whose act or process produces dangerous waste or whose act first causes a dangerous waste to become subject to regulation.

"Genetic properties" means those properties which cause or significantly contribute to mutagenic, teratogenic, or carcinogenic effects in man or wildlife.

"Ground water" means water which fills voids below the land surface and in the earth's crust.

"Halogenated organic compounds" (HOC) means any organic compounds which, as part of their composition, include one or more atoms of fluorine, chlorine, bromine, or iodine which is/are bonded directly to a carbon atom. This definition does not apply to the federal land disposal restrictions of 40 CFR Part 268 which are incorporated by reference at WAC 173-303-140 (2)(a). Note: Additional information on HOCs may be found in *Chemical Testing Methods for Designating Dangerous Waste*, Ecology Publication #97-407.

"Hazardous debris" means debris that contains a hazardous waste listed in WAC 173-303-9903 or 173-303-9904, or that exhibits a characteristic of hazardous waste identified in WAC 173-303-090.

"Hazardous substances" means any liquid, solid, gas, or sludge, including any material, substance, product, commodity, or waste, regardless of quantity, that exhibits any of the physical, chemical or biological properties described in WAC 173-303-090 or 173-303-100.

"Hazardous wastes" means those solid wastes designated by 40 CFR Part 261, and regulated as hazardous and/or mixed waste by the United States EPA. This term will never be abbreviated in this chapter to avoid confusion with the abbreviations "DW" and "EHW." (See also "dangerous waste" and "extremely hazardous waste" definitions.)

"Home scrap metal" is scrap metal as generated by steel mills, foundries, and refineries such as turnings, cuttings, punchings, and borings.

"Ignitable waste" means a dangerous waste that exhibits the characteristic of ignitability described in WAC 173-303-090(5).

"Inactive portion" means that portion of a facility which has not recycled, treated, stored, or disposed dangerous waste after:

The effective date of the waste's designation, for wastes designated under 40 CFR Part 261; and

March 10, 1982, for wastes designated only by this chapter and not designated by 40 CFR Part 261.

"Inactive range" means a military range that is not currently being used, but that is still under military control and considered by the military to be a potential range area, and that has not been put to a new use that is incompatible with range activities.

"Incinerator" means any enclosed device that:

Uses controlled flame combustion and neither meets the criteria for classification as a boiler, sludge dryer, or carbon regeneration unit, nor is listed as an industrial furnace; or

Meets the definition of infrared incinerator or plasma arc incinerator.

"Incompatible waste" means a dangerous waste which is unsuitable for placement in a particular device or facility because it may corrode or decay the containment materials, or is unsuitable for mixing with another waste or material because the mixture might produce heat or pressure, fire or explosion, violent reaction, toxic dusts, fumes, mists, or gases, or flammable fumes or gases.

"Independent qualified registered professional engineer" means a person who is licensed by the state of Washington, or a state which has reciprocity with the state of Washington as defined in RCW 18.43.100, and who is not an employee of the owner or operator of the facility for which construction or modification certification is required. A qualified professional engineer is an engineer with expertise in the specific area for which a certification is given.

"Industrial-furnace" means any of the following enclosed devices that are integral components of manufacturing processes and that use thermal treatment to accomplish recovery of materials or energy: Cement kilns; lime kilns; aggregate kilns; phosphate kilns; blast furnaces; smelting, melting, and refining furnaces (including pyrometallurgical devices such as cupolas, reverberator furnaces, sintering machines, roasters and foundry furnaces); titanium dioxide chloride process oxidation reactors; coke ovens; methane reforming furnaces; combustion devices used in the recovery of sulfur values from spent sulfuric acid; pulping liquor recovery furnaces; combustion devices used in the recovery of sulfur values from spent sulfuric acid; and halogen acid furnaces (HAFs) for the production of acid from halogenated dangerous waste generated by chemical production facilities where the furnace is located on the site of a chemical production facility, the acid product has a halogen acid content of at least 3%, the acid product is used in a manufacturing process, and, except for dangerous waste burned as fuel, dangerous waste fed to the furnace has a minimum halogen content of 20% as-generated. The department may decide to add devices to this list on the basis of one or more of the following factors:

The device is designed and used primarily to accomplish recovery of material products;

The device burns or reduces secondary materials as ingredients

in an industrial process to make a material product;

The device burns or reduces secondary materials as effective substitutes for raw materials in processes using raw materials as principal feedstocks;

The device burns or reduces raw materials to make a material product;

The device is in common industrial use to produce a material product; and

Other factors, as appropriate.

"Infrared incinerator" means any enclosed device that uses electric powered resistance heaters as a source of radiant heat followed by an afterburner using controlled flame combustion and which is not listed as an industrial furnace.

"Inground tank" means a device meeting the definition of "tank" in this section whereby a portion of the tank wall is situated to any degree within the ground, thereby preventing visual inspection of that external surface area of the tank that is in the ground.

"Inner liner" means a continuous layer of material placed inside a tank or container which protects the construction materials of the tank or container from the waste or reagents used to treat the waste.

"Installation inspector" means a person who, by reason of his knowledge of the physical sciences and the principles of engineering, acquired by a professional education and related practical experience, is qualified to supervise the installation of tank systems.

"Interim status permit" means a temporary permit given to TSD facilities which qualify under WAC 173-303-805.

"Knowledge" means sufficient information about a waste to reliably substitute for direct testing of the waste. To be sufficient and reliable, the "knowledge" used must provide information necessary to manage the waste in accordance with the requirements of this chapter.

Note: "Knowledge" may be used by itself or in combination with testing to designate a waste pursuant to WAC 173-303-070 (3)(c), or to obtain a detailed chemical, physical, and/or biological analysis of a waste as required in WAC 173-303-300(2).

"Lamp," also referred to as "universal waste lamp" means any type of high or low pressure bulb or tube portion of an electric lighting device that generates light through the discharge of electricity either directly or indirectly as radiant energy. Universal waste lamps include, but are not limited to, fluorescent, mercury vapor, metal halide, high-pressure sodium and neon. As a reference, it may be assumed that four, four-foot, one-inch diameter unbroken fluorescent tubes are equal to 2.2 pounds in weight.

"Land disposal" means placement in or on the land, except in a corrective action management unit or staging pile, and includes, but is not limited to, placement in a landfill, surface impoundment, waste pile, injection well, land treatment facility, salt dome formation, salt bed formation, underground mine or cave, or placement in a concrete vault, or bunker intended for disposal purposes.

"Landfill" means a disposal facility, or part of a facility, where dangerous waste is placed in or on land and which is not a pile, a land treatment facility, a surface impoundment, or an underground injection well, a salt dome formation, a salt bed formation, an underground mine, a cave, or a corrective action management unit.

"Land treatment" means the practice of applying dangerous waste onto or incorporating dangerous waste into the soil surface so that it will degrade or decompose. If the waste will remain after the facility is closed, this practice is disposal.

"Large quantity handler of universal waste" means a universal waste handler (as defined in this section) who accumulates 11,000 pounds or more total of universal waste (batteries, thermostats, mercury-containing equipment, and lamps calculated collectively) and/or who accumulates more than 2,200 pounds of lamps at any time. This designation as a large quantity handler of universal waste is retained through the end of the calendar year in which 11,000 pounds or more total of universal waste and/or 2,200 pounds of lamps is accumulated.

"Leachable inorganic waste" means solid dangerous waste (i.e., passes paint filter test) that is not an organic/carbonaceous waste and exhibits the toxicity characteristic (dangerous waste numbers D004 to D011, only) under WAC 173-303-090(8).

"Leachate" means any liquid, including any components suspended in the liquid, that has percolated through or drained from dangerous waste.

"Leak-detection system" means a system capable of detecting the failure of either the primary or secondary containment structure or the presence of a release of dangerous waste or accumulated liquid in the secondary containment structure. Such a system must employ operational controls (e.g., daily visual inspections for releases into the secondary containment system of aboveground tanks) or consist of an interstitial monitoring device designed to detect continuously and automatically the failure of the primary or secondary containment structure or the presence of a release of dangerous waste into the secondary containment structure.

"Legal defense costs" means any expenses that an insurer incurs in defending against claims of third parties brought under the terms and conditions of an insurance policy.

"Liner" means a continuous layer of man-made or natural materials which restrict the escape of dangerous waste, dangerous waste constituents, or leachate through the sides, bottom, or berms of a surface impoundment, waste pile, or landfill.

"Major facility" means a facility or activity classified by the department as major.

"Manifest" means the shipping document, prepared in accordance with the requirements of WAC 173-303-180, which is used to identify the quantity, composition, origin, routing, and destination of a dangerous waste while it is being transported to a point of transfer, disposal, treatment, or storage.

"Manufacturing process unit" means a unit which is an integral

and inseparable portion of a manufacturing operation, processing a raw material into a manufacturing intermediate or finished product, reclaiming spent materials or reconditioning components.

"Marine terminal operator" means a person engaged in the business of furnishing wharfage, dock, pier, warehouse, covered and/or open storage spaces, cranes, forklifts, bulk loading and/or unloading structures and landings in connection with a highway or rail carrier and a water carrier. A marine terminal operator includes, but is not limited to, terminals owned by states and their political subdivisions; railroads who perform port terminal services not covered by their line haul rates; common carriers who perform port terminal services; and warehousemen and stevedores who operate port terminal facilities.

"Mercury-containing equipment" means a device or part of a device (excluding batteries, thermostats, and lamps) that contains elemental mercury necessary for its operation. Examples of mercury-containing equipment include thermometers, manometers, and electrical switches.

"Micronutrient fertilizer" means a produced or imported commercial fertilizer that contains commercially valuable concentrations of micronutrients but does not contain commercially valuable concentrations of nitrogen, phosphoric acid, available phosphorous, potash, calcium, magnesium, or sulfur. Micronutrients are boron, chlorine, cobalt, copper, iron, manganese, molybdenum, sodium, and zinc.

"Military" means the Department of Defense (DOD), the Armed Services, Coast Guard, National Guard, Department of Energy (DOE), or other parties under contract or acting as an agent for the foregoing, who handle military munitions.

"Military munitions" means all ammunition products and components produced or used by or for the U.S. Department of Defense or the U.S. Armed Services for national defense and security, including military munitions under the control of the Department of Defense, the U.S. Coast Guard, the U.S. Department of Energy (DOE), and National Guard personnel. The term military munitions includes: Confined gaseous, liquid, and solid propellants, explosives, pyrotechnics, chemical and riot control agents, smokes, and incendiaries used by DOD components, including bulk explosives and chemical warfare agents, chemical munitions, rockets, guided and ballistic missiles, bombs, warheads, mortar rounds, artillery ammunition, small arms ammunition, grenades, mines, torpedoes, depth charges, cluster munitions and dispensers, demolition charges, and devices and components thereof. Military munitions do not include wholly inert items, improvised explosive devices, and nuclear weapons, nuclear devices, and nuclear components thereof. However, the term does include nonnuclear components of nuclear devices, managed under DOE's nuclear weapons program after all required sanitization operations under the Atomic Energy Act of 1954, as amended, have been completed.

"Military range" means designated land and water areas set aside, managed, and used to conduct research on, develop, test, and evaluate military munitions and explosives, other ordnance, or

weapon systems, or to train military personnel in their use and handling. Ranges include firing lines and positions, maneuver areas, firing lanes, test pads, detonation pads, impact areas, and buffer zones with restricted access and exclusionary areas.

"Miscellaneous unit" means a dangerous waste management unit where dangerous waste is treated, stored, or disposed of and that is not a container, tank, surface impoundment, pile, land treatment unit, landfill, incinerator, boiler, industrial furnace, underground injection well with appropriate technical standards under 40 CFR Part 146, containment building, corrective action management unit, temporary unit, staging pile, or unit eligible for a research, development, and demonstration permit under WAC 173-303-809.

"Mixed waste" means a dangerous, extremely hazardous, or acutely hazardous waste that contains both a nonradioactive hazardous component and, as defined by 10 CFR 20.1003, source, special nuclear, or by-product material subject to the Atomic Energy Act of 1954 (42 U.S.C. 2011 et seq.).

"New tank system" or "new tank component" means a tank system or component that will be used for the storage or treatment of dangerous waste and for which installation has commenced after February 3, 1989; except, however, for purposes of WAC 173-303-640 (4) (g) (ii) and 40 CFR 265.193 (g) (2) as adopted by reference in WAC 173-303-400(3), a new tank system is one for which construction commences after February 3, 1989. (See also "existing tank system.")

"New TSD facility" means a facility which began operation or for which construction commenced after November 19, 1980, for wastes designated by 40 CFR Part 261, or August 9, 1982, for wastes designated only by this chapter and not designated by 40 CFR Part 261.

"NIOSH registry" means the registry of toxic effects of chemical substances which is published by the National Institute for Occupational Safety and Health.

"Nonsudden accident" or "nonsudden accidental occurrence" means an unforeseen and unexpected occurrence which takes place over time and involves continuous or repeated exposure.

"Occurrence" means an accident, including continuous or repeated exposure to conditions, which results in bodily injury or property damage which the owner or operator neither expected nor intended to occur.

"Off-specification used oil fuel" means used oil fuel that exceeds any specification level described in Table 1 in WAC 173-303-515.

"Onground tank" means a device meeting the definition of "tank" in this section and that is situated in such a way that the bottom of the tank is on the same level as the adjacent surrounding surface so that the external tank bottom cannot be visually inspected.

"On-site" means the same or geographically contiguous property which may be divided by public or private right of way, provided that the entrance and exit between the properties is at a cross-

roads intersection, and access is by crossing as opposed to going along the right of way. Noncontiguous properties owned by the same person but connected by a right of way which they control and to which the public does not have access, are also considered on-site property.

"Operator" means the person responsible for the overall operation of a facility. (See also "state operator.")

"Oral LD₅₀" means the single dosage in milligrams per kilogram (mg/kg) body weight, when orally administered, which, within 14 days, kills half a group of ten or more white rats each weighing between 200 and 300 grams.

"Organic/carbonaceous waste" means a dangerous waste that contains combined concentrations of greater than ten percent organic/carbonaceous constituents in the waste; organic/carbonaceous constituents are those substances that contain carbon-hydrogen, carbon-halogen, or carbon-carbon chemical bonding.

"Partial closure" means the closure of a dangerous waste management unit in accordance with the applicable closure requirements of WAC 173-303-400 and 173-303-600 through 173-303-695 at a facility that contains other active dangerous waste management units. For example, partial closure may include the closure of a tank (including its associated piping and underlying containment systems), landfill cell, surface impoundment, waste pile, or other dangerous waste management unit, while other units of the same facility continue to operate.

"Permit" means an authorization which allows a person to perform dangerous waste transfer, storage, treatment, or disposal operations, and which typically will include specific conditions for such facility operations. Permits must be issued by one of the following:

The department, pursuant to this chapter;

United States EPA, pursuant to 40 CFR Part 270; or

Another state authorized by EPA, pursuant to 40 CFR Part 271.

"Permit-by-rule" means a provision of this chapter stating that a facility or activity is deemed to have a dangerous waste permit if it meets the requirements of the provision.

"Persistence" means the quality of a material that retains more than half of its initial activity after one year (365 days) in either a dark anaerobic or dark aerobic environment at ambient conditions. Persistent compounds are either halogenated organic compounds (HOC) or polycyclic aromatic hydrocarbons (PAH) as defined in this section.

"Person" means any person, firm, association, county, public or municipal or private corporation, agency, or other entity whatsoever.

"Pesticide" means but is not limited to: Any substance or mixture of substances intended to prevent, destroy, control, repel, or mitigate any insect, rodent, nematode, mollusk, fungus, weed, and any other form of plant or animal life, or virus (except virus on or in living man or other animal) which is normally considered to be a pest or which the department of agriculture may declare to be a pest; any substance or mixture of substances intended to be

used as a plant regulator, defoliant, or desiccant; any substance or mixture of substances intended to be used as spray adjuvant; and, any other substance intended for such use as may be named by the department of agriculture by regulation. Herbicides, fungicides, insecticides, and rodenticides are pesticides for the purposes of this chapter.

"Pile" means any noncontainerized accumulation of solid, nonflowing dangerous waste that is used for treatment or storage.

"Plasma arc incinerator" means any enclosed device using a high intensity electrical discharge or arc as a source of heat followed by an afterburner using controlled flame combustion and which is not listed as an industrial furnace.

"Point source" means any confined and discrete conveyance from which pollutants are or may be discharged. This term includes, but is not limited to, pipes, ditches, channels, tunnels, wells, cracks, containers, rolling stock, concentrated animal feeding operations, or watercraft, but does not include return flows from irrigated agriculture.

"Polycyclic aromatic hydrocarbons" (PAH) means those hydrocarbon molecules composed of two or more fused benzene rings. For purposes of this chapter, the PAHs of concern for designation are: Acenaphthene, acenaphthylene, fluorene, anthracene, fluoranthene, phenanthrene, benzo(a)anthracene, benzo(b)fluoranthene, benzo(k)fluoranthene, pyrene, chrysene, benzo(a)pyrene, dibenz(a,h)anthracene, indeno(1,2,3-c,d)pyrene, benzo(g,h,i)perylene, dibenzo [(a,e), (a,h), (a,i), and (a,l)] pyrenes, and dibenzo(a,j) acridine.

"Post-closure" means the requirements placed upon disposal facilities (e.g., landfills, impoundments closed as disposal facilities, etc.) after closure to ensure their environmental safety for a number of years after closure. (See also "closure.")

"Processed scrap metal" is scrap metal that has been manually or physically altered to either separate it into distinct materials to enhance economic value or to improve the handling of materials. Processed scrap metal includes, but is not limited to, scrap metal which has been baled, shredded, sheared, chopped, crushed, flattened, cut, melted, or separated by metal type (that is, sorted), and fines, drosses and related materials that have been agglomerated. Note: Shredded circuit boards being sent for recycling are not considered processed scrap metal. They are covered under the exclusion from the definition of solid waste for shredded circuit boards being recycled (WAC 173-303-071 (3)(gg)).

"Prompt scrap metal" is scrap metal as generated by the metal working/fabrication industries and includes such scrap metal as turnings, cuttings, punchings, and borings. Prompt scrap is also known as industrial or new scrap metal.

"Publicly owned treatment works" or "POTW" means any device or system, owned by the state or a municipality, which is used in the treatment, recycling, or reclamation of municipal sewage or liquid industrial wastes. This term includes sewers, pipes, or other conveyances only if they convey wastewater to a POTW.

"Qualified ground water scientist" means a scientist or

engineer who has received a baccalaureate or post-graduate degree in the natural sciences or engineering, and has sufficient training and experience in ground water hydrology and related fields to make sound professional judgments regarding ground water monitoring and contaminant fate and transport. Sufficient training and experience may be demonstrated by state registration, professional certifications, or completion of accredited university courses.

"Reactive waste" means a dangerous waste that exhibits the characteristic of reactivity described in WAC 173-303-090(7).

"Reclaim" means to process a material in order to recover useable products, or to regenerate the material. Reclamation is the process of reclaiming.

"Recover" means extract a useable material from a solid or dangerous waste through a physical, chemical, biological, or thermal process. Recovery is the process of recovering.

"Recycle" means to use, reuse, or reclaim a material.

"Recycling unit" is a contiguous area of land, structures and equipment where materials designated as dangerous waste or used oil are placed or processed in order to recover useable products or regenerate the original materials. For the purposes of this definition, "placement" does not mean "storage" when conducted within the provisions of WAC 173-303-120(4). A container, tank, or processing equipment alone does not constitute a unit; the unit includes containers, tanks or other processing equipment, their ancillary equipment and secondary containment system, and the land upon which they are placed.

"Registration number" means the number assigned by the department of ecology to a transporter who owns or leases and operates a ten-day transfer facility within Washington state.

"Regulated unit" means any new or existing surface impoundment, landfill, land treatment area or waste pile that receives any dangerous waste after:

July 26, 1982, for wastes regulated by 40 CFR Part 261;

October 31, 1984 for wastes designated only by this chapter and not regulated by 40 CFR Part 261; or

The date six months after a waste is newly identified by amendments to 40 CFR Part 261 or this chapter which cause the waste to be regulated.

"Release" means any intentional or unintentional spilling, leaking, pouring, emitting, emptying, discharging, injecting, pumping, escaping, leaching, dumping, or disposing of dangerous wastes, or dangerous constituents as defined at WAC 173-303-64610(4), into the environment and includes the abandonment or discarding of barrels, containers, and other receptacles containing dangerous wastes or dangerous constituents and includes the definition of release at RCW 70.105D.020(20).

"Remediation waste" means all solid and dangerous wastes, and all media (including ground water, surface water, soils, and sediments) and debris, that are managed for implementing cleanup.

"Replacement unit" means a landfill, surface impoundment, or waste pile unit from which all or substantially all of the waste is removed, and that is subsequently reused to treat, store, or

dispose of dangerous waste. "Replacement unit" does not apply to a unit from which waste is removed during closure, if the subsequent reuse solely involves the disposal of waste from that unit and other closing units or corrective action areas at the facility, in accordance with an approved closure plan or EPA or state approved corrective action.

"Representative sample" means a sample which can be expected to exhibit the average properties of the sample source.

"Reuse or use" means to employ a material either:

As an ingredient (including use as an intermediate) in an industrial process to make a product (for example, distillation bottoms from one process used as feedstock in another process). However, a material will not satisfy this condition if distinct components of the material are recovered as separate end products (as when metals are recovered from metal-containing secondary materials); or

In a particular function or application as an effective substitute for a commercial product (for example, spent pickle liquor used as phosphorous precipitant and sludge conditioner in wastewater treatment).

"Runoff" means any rainwater, leachate, or other liquid which drains over land from any part of a facility.

"Run-on" means any rainwater, leachate, or other liquid which drains over land onto any part of a facility.

"Satellite accumulation area" means a location at or near any point of generation where hazardous waste is initially accumulated in containers (during routine operations) prior to consolidation at a designated ninety-day accumulation area or storage area. The area must be under the control of the operator of the process generating the waste or secured at all times to prevent improper additions of wastes into the satellite containers.

"Schedule of compliance" means a schedule of remedial measures in a permit including an enforceable sequence of interim requirements leading to compliance with this chapter.

"Scrap metal" means bits and pieces of metal parts (e.g., bars, turnings, rods, sheets, wire) or metal pieces that may be combined together with bolts or soldering (e.g., radiators, scrap automobiles, railroad box cars), which when worn or superfluous can be recycled.

"Sludge" means any solid, semisolid, or liquid waste generated from a municipal, commercial, or industrial wastewater treatment plant, water supply treatment plant, or air pollution control facility. This term does not include the treated effluent from a wastewater treatment plant.

"Sludge dryer" means any enclosed thermal treatment device that is used to dehydrate sludge and that has a maximum total thermal input, excluding the heating value of the sludge itself, of 2,500 Btu/lb of sludge treated on a wet-weight basis.

"Small quantity handler of universal waste" means a universal waste handler (as defined in this section) who does not accumulate 11,000 pounds or more total of universal waste (batteries, thermostats, mercury-containing equipment, and lamps, calculated

collectively) and/or who does not accumulate more than 2,200 pounds of lamps at any time.

"Solid acid waste" means a dangerous waste that exhibits the characteristic of low pH under the corrosivity tests of WAC 173-303-090 (6) (a) (iii).

"Solid waste management unit" or "SWMU" means any discernible location at a facility, as defined for the purposes of corrective action, where solid wastes have been placed at any time, irrespective of whether the location was intended for the management of solid or dangerous waste. Such locations include any area at a facility at which solid wastes, including spills, have been routinely and systematically released. Such units include regulated units as defined by chapter 173-303 WAC.

"Sorbent" means a material that is used to soak up free liquids by either adsorption or absorption, or both. *Sorb* means to either adsorb or absorb, or both.

"Special incinerator ash" means ash residues resulting from the operation of incineration or energy recovery facilities managing municipal solid waste from residential, commercial and industrial establishments, if the ash residues are designated as dangerous waste only by this chapter and not designated as hazardous waste by 40 CFR Part 261.

"Special waste" means any state-only dangerous waste that is solid only (nonliquid, nonaqueous, nongaseous), that is: Corrosive waste (WAC 173-303-090 (6) (b) (ii)), toxic waste that has Category D toxicity (WAC 173-303-100(5)), PCB waste (WAC 173-303-9904 under State Sources), or persistent waste that is not EHW (WAC 173-303-100(6)). Any solid waste that is regulated by the United States EPA as hazardous waste cannot be a special waste.

"Spent material" means any material that has been used and as a result of contamination can no longer serve the purpose for which it was produced without processing.

"Stabilization" and "solidification" means a technique that limits the solubility and mobility of dangerous waste constituents. Solidification immobilizes a waste through physical means and stabilization immobilizes the waste by bonding or chemically reacting with the stabilizing material.

"Staging pile" means an accumulation of solid, nonflowing, remediation waste that is not a containment building or a corrective action management unit and that is used for temporary storage of remediation waste for implementing corrective action under WAC 173-303-646 or other clean up activities.

"State-only dangerous waste" means a waste designated only by this chapter, chapter 173-303 WAC, and is not regulated as a hazardous waste under 40 CFR Part 261.

"State operator" means the person responsible for the overall operation of the state's extremely hazardous waste facility on the Hanford Reservation.

"Storage" means the holding of dangerous waste for a temporary period. "Accumulation" of dangerous waste, by the generator on the site of generation, is not storage as long as the generator complies with the applicable requirements of WAC 173-303-200 and

173-303-201.

"Sudden accident" means an unforeseen and unexpected occurrence which is not continuous or repeated in nature.

"Sump" means any pit or reservoir that meets the definition of tank and those troughs/trenches connected to it that serves to collect dangerous waste for transport to dangerous waste storage, treatment, or disposal facilities; except that as used in the landfill, surface impoundment, and waste pile rules, "sump" means any lined pit or reservoir that serves to collect liquids drained from a leachate collection and removal system or leak detection system for subsequent removal from the system.

"Surface impoundment" means a facility or part of a facility which is a natural topographic depression, man-made excavation, or diked area formed primarily of earthen materials (although it may be lined with man-made materials), and which is designed to hold an accumulation of liquid dangerous wastes or dangerous wastes containing free liquids. The term includes holding, storage, settling, and aeration pits, ponds, or lagoons, but does not include injection wells.

"Tank" means a stationary device designed to contain an accumulation of dangerous waste, and which is constructed primarily of nonearthen materials to provide structural support.

"Tank system" means a dangerous waste storage or treatment tank and its associated ancillary equipment and containment system.

"Temporary unit" means a tank or container that is not an accumulation unit under WAC 173-303-200 and that is used for temporary treatment or storage of remediation waste for implementing corrective action under WAC 173-303-646 or other clean up activities.

"TEQ" means toxicity equivalence, the international method of relating the toxicity of various dioxin/furan congeners to the toxicity of 2,3,7,8-tetrachlorodibenzo-p-dioxin.

"Thermal treatment" means the treatment of dangerous waste in a device which uses elevated temperatures as the primary means to change the chemical, physical, or biological character or composition of the dangerous waste. Examples of thermal treatment processes are incineration, molten salt, pyrolysis, calcination, wet air oxidation, and microwave discharge.

"Thermostat" means a temperature control device that contains metallic mercury in an ampule attached to a bimetal sensing element, and mercury-containing ampules that have been removed from these temperature control devices in compliance with the requirements of WAC 173-303-573 (9)(b)(ii) or (20)(b)(ii).

"TLm₉₆" means the same as "Aquatic LC₅₀."

"Totally enclosed treatment facility" means a facility for treating dangerous waste which is directly connected to a production process and which prevents the release of dangerous waste or dangerous waste constituents into the environment during treatment.

"Toxic" means having the properties to cause or to significantly contribute to death, injury, or illness of man or wildlife.

"Transfer facility" means any transportation related facility including loading docks, parking areas, storage areas, buildings, piers, and other similar areas where shipments of dangerous waste are held, consolidated, or transferred within a period of ten days or less during the normal course of transportation.

"Transport vehicle" means a motor vehicle, water vessel, or rail car used for the transportation of cargo by any mode. Each cargo-carrying body (trailer, railroad freight car, steamship, etc.) is a separate transport vehicle.

"Transportation" means the movement of dangerous waste by air, rail, highway, or water.

"Transporter" means a person engaged in the off-site transportation of dangerous waste.

"Travel time" means the period of time necessary for a dangerous waste constituent released to the soil (either by accident or intent) to enter any on-site or off-site aquifer or water supply system.

"Treatability study" means a study in which a dangerous waste is subjected to a treatment process to determine: Whether the waste is amenable to the treatment process; what pretreatment (if any) is required; the optimal process conditions needed to achieve the desired treatment; the efficiency of a treatment process for a specific waste or wastes; or the characteristics and volumes of residuals from a particular treatment process. Also included in this definition for the purpose of the exemptions contained in WAC 173-303-071 (3) (r) and (s), are liner compatibility, corrosion, and other material compatibility studies and toxicological and health effects studies. A "treatability study" is not a means to commercially treat or dispose of dangerous waste.

"Treatment" means the physical, chemical, or biological processing of dangerous waste to make such wastes nondangerous or less dangerous, safer for transport, amenable for energy or material resource recovery, amenable for storage, or reduced in volume, with the exception of compacting, repackaging, and sorting as allowed under WAC 173-303-400(2) and 173-303-600(3).

"Treatment zone" means a soil area of the unsaturated zone of a land treatment unit within which dangerous wastes are degraded, transformed or immobilized.

"Triple rinsing" means the cleaning of containers in accordance with the requirements of WAC 173-303-160 (2) (b), containers.

"Underground injection" means the subsurface emplacement of fluids through a bored, drilled, or driven well, or through a dug well, where the depth of the dug well is greater than the largest surface dimension.

"Underground tank" means a device meeting the definition of "tank" in this section whose entire surface area is totally below the surface of and covered by the ground.

"Unexploded ordnance (UXO)" means military munitions that have been primed, fused, armed, or otherwise prepared for action, and have been fired, dropped, launched, projected, or placed in such a manner as to constitute a hazard to operations, installation,

personnel, or material and remain unexploded either by malfunction, design, or any other cause.

"Unfit-for-use tank system" means a tank system that has been determined through an integrity assessment or other inspection to be no longer capable of storing or treating dangerous waste without posing a threat of release of dangerous waste to the environment.

"Universal waste" means any of the following dangerous wastes that are subject to the universal waste requirements of WAC 173-303-573:

Batteries as described in WAC 173-303-573(2);
Thermostats as described in WAC 173-303-573(3);
Lamps as described in WAC 173-303-573(5); and
Mercury-containing equipment as described in WAC 173-303-573(4).

"Universal waste handler":

Means:

A generator (as defined in this section) of universal waste;
or

The owner or operator of a facility, including all contiguous property, that receives universal waste from other universal waste handlers, accumulates universal waste, and sends universal waste to another universal waste handler, to a destination facility, or to a foreign destination.

Does not mean:

A person who treats (except under the provisions of WAC 173-303-573 (9) (a), (b), or (c) or (20) (a), (b), or (c)) disposes of, or recycles universal waste; or

A person engaged in the off-site transportation of universal waste by air, rail, highway, or water, including a universal waste transfer facility.

"Universal waste transfer facility" means any transportation-related facility including loading docks, parking areas, storage areas and other similar areas where shipments of universal waste are held during the normal course of transportation for ten days or less.

"Universal waste transporter" means a person engaged in the off-site transportation of universal waste by air, rail, highway, or water.

"Unsaturated zone" means the zone between the land surface and the water table.

"Uppermost aquifer" means the geological formation nearest the natural ground surface that is capable of yielding ground water to wells or springs. It includes lower aquifers that are hydraulically interconnected with this aquifer within the facility property boundary.

"Used oil" means any oil that has been refined from crude oil, or any synthetic oil, that has been used and as a result of such use is contaminated by physical or chemical impurities.

"Vessel" includes every description of watercraft, used or capable of being used as a means of transportation on the water.

"Waste-derived fertilizer" means a commercial fertilizer that is derived in whole or in part from solid waste as defined in

chapter 70.95 or 70.105 RCW, or rules adopted thereunder, but does not include fertilizers derived from biosolids or biosolid products regulated under chapter 70.95J RCW or wastewaters regulated under chapter 90.48 RCW.

"Wastewater treatment unit" means a device that:

Is part of a wastewater treatment facility which is subject to regulation under either:

Section 402 or section 307(b) of the Federal Clean Water Act;

or

Chapter 90.48 RCW, State Water Pollution Control Act, provided that the waste treated at the facility is a state-only dangerous waste; and

Handles dangerous waste in the following manner:

Receives and treats or stores an influent wastewater; or

Generates and accumulates or treats or stores a wastewater treatment sludge; and

Meets the definition of tank or tank system in this section.

"Water or rail (bulk shipment)" means the bulk transportation of dangerous waste which is loaded or carried on board a vessel or railcar without containers or labels.

"Zone of engineering control" means an area under the control of the owner/operator that, upon detection of a dangerous waste release, can be readily cleaned up prior to the release of dangerous waste or dangerous constituents to ground water or surface water.

Any terms used in this chapter which have not been defined in this section have either the same meaning as set forth in Title 40 CFR Parts 260, 264, 270, and 124 or else have their standard, technical meaning.

As used in this chapter, words in the masculine gender also include the feminine and neuter genders, words in the singular include the plural, and words in the plural include the singular.

AMENDATORY SECTION (Amending Order 03-10, filed 11/30/04, effective 1/1/05)

WAC 173-303-071 Excluded categories of waste. (1) Purpose. Certain categories of waste have been excluded from the requirements of chapter 173-303 WAC, except for WAC 173-303-050, because they generally are not dangerous waste, are regulated under other state and federal programs, or are recycled in ways which do not threaten public health or the environment. WAC 173-303-071 describes these excluded categories of waste.

(2) Excluding wastes. Any persons who generate a common class of wastes and who seek to categorically exclude such class of wastes from the requirements of this chapter must comply with the applicable requirements of WAC 173-303-072. No waste class will be excluded if any of the wastes in the class are regulated as

hazardous waste under 40 CFR Part 261.

(3) Exclusions. The following categories of waste are excluded from the requirements of chapter 173-303 WAC, except for WAC 173-303-050, 173-303-145, and 173-303-960, and as otherwise specified:

(a) (i) Domestic sewage; and

(ii) Any mixture of domestic sewage and other wastes that passes through a sewer system to a publicly owned treatment works (POTW) for treatment provided:

(A) The generator or owner/operator has obtained a state waste discharge permit issued by the department, a temporary permit obtained pursuant to RCW 90.48.200, or pretreatment permit (or written discharge authorization) from a local sewage utility delegated pretreatment program responsibilities pursuant to RCW 90.48.165;

(B) The waste discharge is specifically authorized in a state waste discharge permit, pretreatment permit or written discharge authorization, or in the case of a temporary permit the waste is accurately described in the permit application;

(C) The waste discharge is not prohibited under 40 CFR Part 403.5; and

(D) The waste prior to mixing with domestic sewage must not exhibit dangerous waste characteristics for ignitability, corrosivity, reactivity, or toxicity as defined in WAC 173-303-090, and must not meet the dangerous waste criteria for toxic dangerous waste or persistent dangerous waste under WAC 173-303-100, unless the waste is treatable in the publicly owned treatment works (POTW) where it will be received. This exclusion does not apply to the generation, treatment, storage, recycling, or other management of dangerous wastes prior to discharge into the sanitary sewage system;

(b) Industrial wastewater discharges that are point-source discharges subject to regulation under Section 402 of the Clean Water Act. This exclusion does not apply to the collection, storage, or treatment of industrial waste-waters prior to discharge, nor to sludges that are generated during industrial wastewater treatment. Owners or operators of certain wastewater treatment facilities managing dangerous wastes may qualify for a permit-by-rule pursuant to WAC 173-303-802(5);

(c) Household wastes, including household waste that has been collected, transported, stored, or disposed. Wastes that are residues from or are generated by the management of household wastes (e.g., leachate, ash from burning of refuse-derived fuel) are not excluded by this provision. "Household wastes" means any waste material (including, but not limited to, garbage, trash, and sanitary wastes in septic tanks) derived from households (including single and multiple residences, hotels and motels, bunkhouses, ranger stations, crew quarters, campgrounds, picnic grounds, and day-use recreation areas). A resource recovery facility managing municipal solid waste will not be deemed to be treating, storing, disposing of, or otherwise managing dangerous wastes for the purposes of regulation under this chapter, if such facility:

(i) Receives and burns only:

(A) Household waste (from single and multiple dwellings, hotels, motels, and other residential sources); and

(B) Solid waste from commercial or industrial sources that does not contain dangerous waste; and

(ii) Such facility does not accept dangerous wastes and the owner or operator of such facility has established contractual requirements or other appropriate notification or inspection procedures to assure that dangerous wastes are not received at or burned in such facility;

(d) Agricultural crops and animal manures which are returned to the soil as fertilizers;

(e) Asphaltic materials designated only for the presence of PAHs by WAC 173-303-100(6). For the purposes of this exclusion, asphaltic materials means materials that have been used for structural and construction purposes (e.g., roads, dikes, paving) that were produced from mixtures of oil and sand, gravel, ash or similar substances;

(f) Roofing tars and shingles, except that these wastes are not excluded if mixed with wastes listed in WAC 173-303-081 or 173-303-082, or if they exhibit any of the characteristics specified in WAC 173-303-090;

(g) Treated wood waste and wood products including:

(i) Arsenical-treated wood that fails the test for the toxicity characteristic of WAC 173-303-090(8) (dangerous waste numbers D004 through D017 only) or that fails any state criteria, if the waste is generated by persons who utilize the arsenical-treated wood for the materials' intended end use. Intended end use means the wood product must have been used in typical treated wood applications (for example, fence posts, decking, poles, and timbers).

(ii) Wood treated with other preservatives provided such treated wood and wood waste (for example, sawdust and shavings) are, within one hundred eighty days after becoming waste:

(A) Disposed of at a landfill that is permitted in accordance with chapter 173-350 WAC, Solid waste handling standards, or chapter 173-351 WAC, criteria for municipal solid waste landfills, and provided that such wood is neither a listed waste under WAC 173-303-9903 and 173-303-9904 nor a TCLP waste under WAC 173-303-090(8); or

(B) Sent to a facility that will legitimately treat or recycle the treated wood waste, and manage any residue in accordance with that state's dangerous waste regulations; or

(C) Sent off-site to a permitted TSD facility or placed in an on-site facility which is permitted by the department under WAC 173-303-800 through 173-303-845. In addition, creosote-treated wood is excluded when burned for energy recovery in an industrial furnace or boiler that has an order of approval issued pursuant to RCW 70.94.152 by ecology or a local air pollution control authority to burn creosote treated wood.

(h) Irrigation return flows;

(i) Reserve;

- (j) Mining overburden returned to the mining site;
- (k) Polychlorinated biphenyl (PCB) wastes:
 - (i) PCB wastes whose disposal is regulated by EPA under 40 CFR 761.60 (Toxic Substances Control Act) and that are dangerous either because:
 - (A) They fail the test for toxicity characteristic (WAC 173-303-090(8), Dangerous waste codes D018 through D043 only); or
 - (B) Because they are designated only by this chapter and not designated by 40 CFR Part 261, are exempt from regulation under this chapter except for WAC 173-303-505 through 173-303-525, 173-303-960, those sections specified in subsection (3) of this section, and 40 CFR Part 266;
 - (ii) Wastes that would be designated as dangerous waste under this chapter solely because they are listed as WPCB under WAC 173-303-9904 when such wastes are stored and disposed in a manner equivalent to the requirements of 40 CFR Part 761 Subpart D for PCB concentrations of 50 ppm or greater.
 - (l) Samples:
 - (i) Except as provided in (l)(ii) of this subsection, a sample of solid waste or a sample of water, soil, or air, which is collected for the sole purpose of testing to determine its characteristics or composition, is not subject to any requirements of this chapter, when:
 - (A) The sample is being transported to a lab for testing or being transported to the sample collector after testing; or
 - (B) The sample is being stored by the sample collector before transport, by the laboratory before testing, or by the laboratory after testing prior to return to the sample collector; or
 - (C) The sample is being stored temporarily in the laboratory after testing for a specific purpose (for example, until conclusion of a court case or enforcement action).
 - (ii) In order to qualify for the exemptions in (l)(i) of this subsection, a sample collector shipping samples to a laboratory and a laboratory returning samples to a sample collector must:
 - (A) Comply with United States Department of Transportation (DOT), United States Postal Service (USPS), or any other applicable shipping requirements; or
 - (B) Comply with the following requirements if the sample collector determines that DOT or USPS, or other shipping requirements do not apply:
 - (I) Assure that the following information accompanies the sample:
 - (AA) The sample collector's name, mailing address, and telephone number;
 - (BB) The laboratory's name, mailing address, and telephone number;
 - (CC) The quantity of the sample;
 - (DD) The date of shipment;
 - (EE) A description of the sample; and
 - (II) Package the sample so that it does not leak, spill, or vaporize from its packaging.
 - (iii) This exemption does not apply if the laboratory

determines that the waste is dangerous but the laboratory is no longer meeting any of the conditions stated in (l)(i) of this subsection;

(m) Reserve;

(n) Dangerous waste generated in a product or raw material storage tank, a product or raw material transport vehicle or vessel, a product or raw material pipeline, or in a manufacturing process unit or an associated nonwaste-treatment-manufacturing unit until it exits the unit in which it was generated. This exclusion does not apply to surface impoundments, nor does it apply if the dangerous waste remains in the unit more than ninety days after the unit ceases to be operated for manufacturing, or for storage or transportation of product or raw materials;

(o) Waste pickle liquor sludge generated by lime stabilization of spent pickle liquor from the iron and steel industry (NAICS codes 331111 and 332111), except that these wastes are not excluded if they exhibit one or more of the dangerous waste criteria (WAC 173-303-100) or characteristics (WAC 173-303-090);

(p) Wastes from burning any of the materials exempted from regulation by WAC 173-303-120 (2)(a)(vii) and (viii). These wastes are not excluded if they exhibit one or more of the dangerous waste characteristics or criteria;

(q) As of January 1, 1987, secondary materials that are reclaimed and returned to the original process or processes in which they were generated where they are reused in the production process provided:

(i) Only tank storage is involved, and the entire process through completion of reclamation is closed by being entirely connected with pipes or other comparable enclosed means of conveyance;

(ii) Reclamation does not involve controlled flame combustion (such as occurs in boilers, industrial furnaces, or incinerators);

(iii) The secondary materials are never accumulated in such tanks for over twelve months without being reclaimed;

(iv) The reclaimed material is not used to produce a fuel, or used to produce products that are used in a manner constituting disposal; and

(v) A generator complies with the requirements of chapter 173-303 WAC for any residues (e.g., sludges, filters, etc.) produced from the collection, reclamation, and reuse of the secondary materials.

(r) Treatability study samples.

(i) Except as provided in (r)(ii) of this subsection, persons who generate or collect samples for the purpose of conducting treatability studies as defined in WAC 173-303-040 are not subject to the requirements of WAC 173-303-180, 173-303-190, and 173-303-200 (1)(a), nor are such samples included in the quantity determinations of WAC 173-303-070 (7) and (8) and 173-303-201 when:

(A) The sample is being collected and prepared for transportation by the generator or sample collector; or

(B) The sample is being accumulated or stored by the generator or sample collector prior to transportation to a laboratory or

testing facility; or

(C) The sample is being transported to the laboratory or testing facility for the purpose of conducting a treatability study; or

(D) The sample or waste residue is being transported back to the original generator from the laboratory or testing facility.

(ii) The exemption in (r)(i) of this subsection is applicable to samples of dangerous waste being collected and shipped for the purpose of conducting treatability studies provided that:

(A) The generator or sample collector uses (in "treatability studies") no more than 10,000 kg of media contaminated with nonacute dangerous waste, 1000 kg of nonacute dangerous waste other than contaminated media, 1 kg of acutely hazardous waste, 2500 kg of media contaminated with acutely hazardous waste for each process being evaluated for each generated waste stream; and

(B) The mass of each sample shipment does not exceed 10,000 kg; the 10,000 kg quantity may be all media contaminated with nonacute dangerous waste or may include 2500 kg of media contaminated with acute hazardous waste, 1000 kg of dangerous waste, and 1 kg of acutely hazardous waste; and

(C) The sample must be packaged so that it will not leak, spill, or vaporize from its packaging during shipment and the requirements of (r)(ii)(C)(I) or (II) of this subsection are met.

(I) The transportation of each sample shipment complies with United States Department of Transportation (DOT), United States Postal Service (USPS), or any other applicable shipping requirements; or

(II) If the DOT, USPS, or other shipping requirements do not apply to the shipment of the sample, the following information must accompany the sample:

(AA) The name, mailing address, and telephone number of the originator of the sample;

(BB) The name, address, and telephone number of the laboratory or testing facility that will perform the treatability study;

(CC) The quantity of the sample;

(DD) The date of shipment; and

(EE) A description of the sample, including its dangerous waste number.

(D) The sample is shipped, within ninety days of being generated or of being taken from a stream of previously generated waste, to a laboratory or testing facility which is exempt under (s) of this subsection or has an appropriate final facility permit or interim status; and

(E) The generator or sample collector maintains the following records for a period ending three years after completion of the treatability study:

(I) Copies of the shipping documents;

(II) A copy of the contract with the facility conducting the treatability study;

(III) Documentation showing:

(AA) The amount of waste shipped under this exemption;

(BB) The name, address, and EPA/state identification number of

the laboratory or testing facility that received the waste;

(CC) The date the shipment was made; and

(DD) Whether or not unused samples and residues were returned to the generator.

(F) The generator reports the information required under (r) (ii) (E) (III) of this subsection in its annual report.

(iii) The department may grant requests, on a case-by-case basis, for up to an additional two years for treatability studies involving bioremediation. The department may grant requests on a case-by-case basis for quantity limits in excess of those specified in (r) (ii) (A) and (B) of this subsection and (s) (iv) of this subsection, for up to an additional 5000 kg of media contaminated with nonacute dangerous waste, 500 kg of nonacute dangerous waste, 1 kg of acute hazardous waste, and 2500 kg of media contaminated with acute hazardous waste or for up to an additional 10,000 kg of wastes regulated only by this chapter and not regulated by 40 CFR Part 261, to conduct further treatability study evaluation:

(A) In response to requests for authorization to ship, store and conduct treatability studies on additional quantities in advance of commencing treatability studies. Factors to be considered in reviewing such requests include the nature of the technology, the type of process, (e.g., batch versus continuous), size of the unit undergoing testing (particularly in relation to scale-up considerations), the time/quantity of material required to reach steady state operating conditions, or test design considerations such as mass balance calculations.

(B) In response to requests for authorization to ship, store, and conduct treatability studies on additional quantities after initiation or completion of initial treatability studies, when:

There has been an equipment or mechanical failure during the conduct of a treatability study; there is a need to verify the results of previously conducted treatability study; there is a need to study and analyze alternative techniques within a previously evaluated treatment process; or there is a need to do further evaluation of an ongoing treatability study to determine final specifications for treatment.

(C) The additional quantities and time frames allowed in (r) (iii) (A) and (B) of this subsection are subject to all the provisions in (r) (i) and (r) (ii) (C) through (F) of this subsection. The generator or sample collector must apply to the department where the sample is collected and provide in writing the following information:

(I) The reason the generator or sample collector requires additional time or quantity of sample for the treatability study evaluation and the additional time or quantity needed;

(II) Documentation accounting for all samples of dangerous waste from the waste stream which have been sent for or undergone treatability studies including the date each previous sample from the waste stream was shipped, the quantity of each previous shipment, the laboratory or testing facility to which it was shipped, what treatability study processes were conducted on each sample shipped, and the available results of each treatability

study;

(III) A description of the technical modifications or change in specifications which will be evaluated and the expected results;

(IV) If such further study is being required due to equipment or mechanical failure, the applicant must include information regarding the reason for the failure or breakdown and also include what procedures or equipment improvements have been made to protect against further breakdowns; and

(V) Such other information that the department considers necessary.

(s) Samples undergoing treatability studies at laboratories and testing facilities. Samples undergoing treatability studies and the laboratory or testing facility conducting such treatability studies (to the extent such facilities are not otherwise subject to chapter 70.105 RCW) are not subject to the requirements of this chapter, except WAC 173-303-050, 173-303-145, and 173-303-960 provided that the conditions of (s)(i) through (xiii) of this subsection are met. A mobile treatment unit (MTU) may qualify as a testing facility subject to (s)(i) through (xiii) of this subsection. Where a group of MTUs are located at the same site, the limitations specified in (s)(i) through (xiii) of this subsection apply to the entire group of MTUs collectively as if the group were one MTU.

(i) No less than forty-five days before conducting treatability studies the laboratory or testing facility notifies the department in writing that it intends to conduct treatability studies under this subsection.

(ii) The laboratory or testing facility conducting the treatability study has an EPA/state identification number.

(iii) No more than a total of 10,000 kg of "as received" media contaminated with nonacute dangerous waste, 2500 kg of media contaminated with acute hazardous waste or 250 kg of other "as received" dangerous waste is subject to initiation of treatment in all treatability studies in any single day. "As received" waste refers to the waste as received in the shipment from the generator or sample collector.

(iv) The quantity of "as received" dangerous waste stored at the facility for the purpose of evaluation in treatability studies does not exceed 10,000 kg, the total of which can include 10,000 kg of media contaminated with nonacute dangerous waste, 2500 kg of media contaminated with acute hazardous waste, 1000 kg of nonacute dangerous wastes other than contaminated media, and 1 kg of acutely hazardous waste. This quantity limitation does not include treatment materials (including nondangerous solid waste) added to "as received" dangerous waste.

(v) No more than ninety days have elapsed since the treatability study for the sample was completed, or no more than one year (two years for treatability studies involving bioremediation) has elapsed since the generator or sample collector shipped the sample to the laboratory or testing facility, whichever date first occurs. Up to 500 kg of treated material from a particular waste stream from treatability studies may be archived

for future evaluation up to five years from the date of initial receipt. Quantities of materials archived are counted against the total storage limit for the facility.

(vi) The treatability study does not involve the placement of dangerous waste on the land or open burning of dangerous waste.

(vii) The laboratory or testing facility maintains records for three years following completion of each study that show compliance with the treatment rate limits and the storage time and quantity limits. The following specific information must be included for each treatability study conducted:

(A) The name, address, and EPA/state identification number of the generator or sample collector of each waste sample;

(B) The date the shipment was received;

(C) The quantity of waste accepted;

(D) The quantity of "as received" waste in storage each day;

(E) The date the treatment study was initiated and the amount of "as received" waste introduced to treatment each day;

(F) The date the treatability study was concluded;

(G) The date any unused sample or residues generated from the treatability study were returned to the generator or sample collector or, if sent to a designated TSD facility, the name of the TSD facility and its EPA/state identification number.

(viii) The laboratory or testing facility keeps, on-site, a copy of the treatability study contract and all shipping papers associated with the transport of treatability study samples to and from the facility for a period ending three years from the completion date of each treatability study.

(ix) The laboratory or testing facility prepares and submits a report to the department by March 15 of each year that estimates the number of studies and the amount of waste expected to be used in treatability studies during the current year, and includes the following information for the previous calendar year:

(A) The name, address, and EPA/state identification number of the laboratory or testing facility conducting the treatability studies;

(B) The types (by process) of treatability studies conducted;

(C) The names and addresses of persons for whom studies have been conducted (including their EPA/state identification numbers);

(D) The total quantity of waste in storage each day;

(E) The quantity and types of waste subjected to treatability studies;

(F) When each treatability study was conducted;

(G) The final disposition of residues and unused sample from each treatability study.

(x) The laboratory or testing facility determines whether any unused sample or residues generated by the treatability study are dangerous waste under WAC 173-303-070 and if so, are subject to the requirements of this chapter, unless the residues and unused samples are returned to the sample originator under the exemption in (r) of this subsection.

(xi) The laboratory or testing facility notifies the department by letter when it is no longer planning to conduct any

treatability studies at the site.

(xii) The date the sample was received, or if the treatability study has been completed, the date of the treatability study, is marked and clearly visible for inspection on each container.

(xiii) While being held on site, each container and tank is labeled or marked clearly with the words "dangerous waste" or "hazardous waste." Each container or tank must also be marked with a label or sign which identifies the major risk(s) associated with the waste in the container or tank for employees, emergency response personnel and the public.

Note: If there is already a system in use that performs this function in accordance with local, state, or federal regulations, then such system will be adequate.

(t) Petroleum-contaminated media and debris that fail the test for the toxicity characteristic of WAC 173-303-090(8) (dangerous waste numbers D018 through D043 only) and are subject to the corrective action regulations under 40 CFR Part 280.

(u) Special incinerator ash (as defined in WAC 173-303-040).

(v) Wood ash that would designate solely for corrosivity by WAC 173-303-090 (6)(a)(iii). For the purpose of this exclusion, wood ash means ash residue and emission control dust generated from the combustion of untreated wood, wood treated solely with creosote, and untreated wood fiber materials including, but not limited to, wood chips, saw dust, tree stumps, paper, cardboard, residuals from waste fiber recycling, deinking rejects, and associated wastewater treatment solids. This exclusion allows for the use of auxiliary fuels including, but not limited to, oils, gas, coal, and other fossil fuels in the combustion process.

(w)(i) Spent wood preserving solutions that have been reclaimed and are reused for their original intended purpose; and

(ii) Wastewaters from the wood preserving process that have been reclaimed and are reused to treat wood.

(iii) Prior to reuse, the wood preserving wastewaters and spent wood preserving solutions described in (w)(i) and (ii) of this subsection, so long as they meet all of the following conditions:

(A) The wood preserving wastewaters and spent wood preserving solutions are reused on-site at water borne plants in the production process for their original intended purpose;

(B) Prior to reuse, the wastewaters and spent wood preserving solutions are managed to prevent release to either land or ground water or both;

(C) Any unit used to manage wastewaters and/or spent wood preserving solutions prior to reuse can be visually or otherwise determined to prevent such releases;

(D) Any drip pad used to manage the wastewaters and/or spent wood preserving solutions prior to reuse complies with the standards in Part 265, Subpart W which is incorporated by reference at WAC 173-303-400 (3)(a), regardless of whether the plant generates a total of less than 220 pounds/month of dangerous waste; and

(E) Prior to operating pursuant to this exclusion, the plant owner or operator submits to the department a one-time notification

stating that the plant intends to claim the exclusion, giving the date on which the plant intends to begin operating under the exclusion, and containing the following language: "I have read the applicable regulation establishing an exclusion for wood preserving wastewaters and spent wood preserving solutions and understand it requires me to comply at all times with the conditions set out in the regulation." The plant must maintain a copy of that document in its on-site records for a period of no less than three years from the date specified in the notice. The exclusion applies only so long as the plant meets all of the conditions. If the plant goes out of compliance with any condition, it may apply to the department for reinstatement. The department may reinstate the exclusion upon finding that the plant has returned to compliance with all conditions and that violations are not likely to recur.

(F) Additional reports.

(I) Upon determination by the department that the storage of wood preserving wastewaters and spent wood preserving solutions in tanks and/or containers poses a threat to public health or the environment, the department may require the owner/operator to provide additional information regarding the integrity of structures and equipment used to store wood preserving wastewaters and spent wood preserving solutions. This authority applies to tanks and secondary containment systems used to store wood preserving wastewaters and spent wood preserving solutions in tanks and containers. The department's determination of a threat to public health or the environment may be based upon observations of factors that would contribute to spills or releases of wood preserving wastewaters and spent wood preserving solutions or the generation of hazardous by-products. Such observations may include, but are not limited to, leaks, severe corrosion, structural defects or deterioration (cracks, gaps, separation of joints), inability to completely inspect tanks or structures, or concerns about the age or design specification of tanks.

(II) When required by the department, a qualified, independent professional engineer registered to practice in Washington state must perform the assessment of the integrity of tanks or secondary containment systems.

(III) Requirement for facility repairs and improvements. If, upon evaluation of information obtained by the department under (w) (iii) (F) (I) of this subsection, it is determined that repairs or structural improvements are necessary in order to eliminate threats, the department may require the owner/operator to discontinue the use of the tank system or container storage unit and remove the wood preserving wastewaters and spent wood preserving solutions until such repairs or improvements are completed and approved by the department.

(x) Nonwastewater splash condenser dross residue from the treatment of K061 in high temperature metals recovery units, provided it is shipped in drums (if shipped) and not land disposed before recovery.

(y) Used oil filters that are recycled in accordance with WAC 173-303-120, as used oil and scrap metal.

(z) Used oil re-refining distillation bottoms that are used as feedstock to manufacture asphalt products.

(aa) Wastes that fail the test for the toxicity characteristic in WAC 173-303-090 because chromium is present or are listed in WAC 173-303-081 or 173-303-082 due to the presence of chromium. The waste must not designate for any other characteristic under WAC 173-303-090, for any of the criteria specified in WAC 173-303-100, and must not be listed in WAC 173-303-081 or 173-303-082 due to the presence of any constituent from WAC 173-303-9905 other than chromium. The waste generator must be able to demonstrate that:

(i) The chromium in the waste is exclusively (or nearly exclusively) trivalent chromium; and

(ii) The waste is generated from an industrial process that uses trivalent chromium exclusively (or nearly exclusively) and the process does not generate hexavalent chromium; and

(iii) The waste is typically and frequently managed in nonoxidizing environments.

(bb) (i) Nonwastewater residues, such as slag, resulting from high temperature metals recovery (HTMR) processing of K061, K062 or F006 waste, in units identified as rotary kilns, flame reactors, electric furnaces, plasma arc furnaces, slag reactors, rotary hearth furnace/electric furnace combinations or industrial furnaces (as defined in WAC 173-303-040 - blast furnaces, smelting, melting and refining furnaces, and other devices the department may add to the list - of the definition for "industrial furnace"), that are disposed in subtitle D units, provided that these residues meet the generic exclusion levels identified in the tables in this paragraph for all constituents, and exhibit no characteristics of dangerous waste. Testing requirements must be incorporated in a facility's waste analysis plan or a generator's self-implementing waste analysis plan; at a minimum, composite samples of residues must be collected and analyzed quarterly and/or when the process or operation generating the waste changes. Persons claiming this exclusion in an enforcement action will have the burden of proving by clear and convincing evidence that the material meets all of the exclusion requirements.

Constituent	Maximum for any single composite sample-TCLP (mg/l)
-------------	--

Generic exclusion levels for K061
and K062 nonwastewater HTMR residues

Antimony	0.10
Arsenic	0.50
Barium	7.6
Beryllium	0.010
Cadmium	0.050
Chromium (total)	0.33
(2)Lead	0.15
Mercury	0.009
Nickel	1.0
Selenium	0.16
Silver	0.30
Thallium	0.020
Zinc	70

Generic exclusion levels for
F006 nonwastewater HTMR residues

Antimony	0.10
Arsenic	0.50
Barium	7.6
Beryllium	0.010
Cadmium	0.050
Chromium (total)	0.33
Cyanide (total) (mg/kg)	1.8
Lead	0.15
Mercury	0.009
Nickel	1.0
Selenium	0.16
Silver	0.30
Thallium	0.020
Zinc	70

(ii) A one-time notification and certification must be placed in the facility's files and sent to the department for K061, K062 or F006 HTMR residues that meet the generic exclusion levels for all constituents and do not exhibit any characteristics that are sent to subtitle D units. The notification and certification that is placed in the generator's or treater's files must be updated if the process or operation generating the waste changes and/or if the subtitle D unit receiving the waste changes. However, the generator or treater need only notify the department on an annual basis if such changes occur. Such notification and certification should be sent to the department by the end of the calendar year, but no later than December 31. The notification must include the following information: The name and address of the subtitle D unit receiving the waste shipments; the dangerous waste number(s) and treatability group(s) at the initial point of generation; and, the treatment standards applicable to the waste at the initial point of generation. The certification must be signed by an authorized representative and must state as follows: "I certify under penalty of law that the generic exclusion levels for all constituents have been met without impermissible dilution and that no characteristic of dangerous waste is exhibited. I am aware that there are significant penalties for submitting a false certification, including the possibility of fine and imprisonment." These wastes are not excluded if they exhibit one or more of the dangerous waste characteristics (WAC 173-303-090) or criteria (WAC 173-303-100).

(cc)(i) Oil-bearing hazardous secondary materials (that is, sludges, by-products, or spent materials) that are generated at a petroleum refinery (NAICS code 324110) and are inserted into the petroleum refining process (NAICS code 324110 - including, but not limited to, distillation, catalytic cracking, fractionation, or thermal cracking units (that is, cokers)) unless the material is placed on the land, or speculatively accumulated before being so recycled. Materials inserted into thermal cracking units are excluded under this paragraph: Provided, That the coke product also does not exhibit a characteristic of hazardous waste. Oil-bearing hazardous secondary materials may be inserted into the same petroleum refinery where they are generated, or sent directly to

another petroleum refinery, and still be excluded under this provision. Except as provided in (cc) (ii) of this subsection, oil-bearing hazardous secondary materials generated elsewhere in the petroleum industry (that is, from sources other than petroleum refineries) are not excluded under this section. Residuals generated from processing or recycling materials excluded under this paragraph, where such materials as generated would have otherwise met a listing under WAC 173-303-081 and 173-303-082, are designated as F037 listed wastes when disposed of or intended for disposal.

(ii) Recovered oil that is recycled in the same manner and with the same conditions as described in (cc)(i) of this subsection. Recovered oil is oil that has been reclaimed from secondary materials (including wastewater) generated from normal petroleum industry practices, including refining, exploration and production, bulk storage, and transportation incident thereto (NAICS codes 211111, 211112, 213111, 213112, 541360, 237120, 238910, 324110, 486110, 486910, 486210, 221210, 486210, 487110, 488210, 488999, 722310, 424710, 454311, 454312, 424720, 425110, 425120). Recovered oil does not include oil-bearing hazardous wastes listed in WAC 173-303-081 and 173-303-082; however, oil recovered from such wastes may be considered recovered oil. Recovered oil does not include used oil as defined in WAC 173-303-040.

(dd) Dangerous waste Nos. K060, K087, K141, K142, K143, K144, K145, K147, and K148, and any wastes from the coke by-products processes that are dangerous only because they exhibit the toxicity characteristic (TC) specified in WAC 173-303-090(8) when, subsequent to generation, these materials are recycled to coke ovens, to the tar recovery process as a feedstock to produce coal tar, or mixed with coal tar prior to the tar's sale or refining. This exclusion is conditioned on there being no land disposal of the wastes from the point they are generated to the point they are recycled to coke ovens or tar recovery or refining processes, or mixed with coal tar.

(ee) Biological treatment sludge from the treatment of one of the following wastes listed in WAC 173-303-9904 - organic waste (including heavy ends, still bottoms, light ends, spent solvents, filtrates, and decantates) from the production of carbamates and carbamoyl oximes (Dangerous Waste No. K156), and wastewaters from the production of carbamates and carbamoyl oximes (Dangerous Waste No. K157) unless it exhibits one or more of the characteristics or criteria of dangerous waste.

(ff) Excluded scrap metal (processed scrap metal, unprocessed home scrap metal, and unprocessed prompt scrap metal) being recycled.

(gg) Shredded circuit boards being recycled: Provided, That they are:

(i) Stored in containers sufficient to prevent a release to the environment prior to recovery; and

(ii) Free of mercury switches, mercury relays and nickel-cadmium batteries and lithium batteries.

(hh) Petrochemical recovered oil from an associated organic chemical manufacturing facility, where the oil is to be inserted into the petroleum refining process (NAICS code 324110) along with normal petroleum refinery process streams, provided:

(i) The oil is hazardous only because it exhibits the characteristic of ignitability (as defined in WAC 173-303-090(5) and/or toxicity for benzene (WAC 173-303-090(8), waste code D018); and

(ii) The oil generated by the organic chemical manufacturing facility is not placed on the land, or speculatively accumulated before being recycled into the petroleum refining process.

An "associated organic chemical manufacturing facility" is a facility where the primary NAICS code is 325110, 325120, 325188, 325192, 325193, or 325199, but where operations may also include NAICS codes 325211, 325212, 325110, 325132, 325192; and is physically colocated with a petroleum refinery; and where the petroleum refinery to which the oil being recycled is returned also provides hydrocarbon feedstocks to the organic chemical manufacturing facility. "Petrochemical recovered oil" is oil that has been reclaimed from secondary materials (that is, sludges, by-products, or spent materials, including wastewater) from normal organic chemical manufacturing operations, as well as oil recovered from organic chemical manufacturing processes.

(ii) Spent caustic solutions from petroleum refining liquid treating processes used as a feedstock to produce cresylic or naphthenic acid unless the material is placed on the land, or accumulated speculatively as defined in WAC 173-303-016(5).

(jj) Catalyst inert support media separated from one of the following wastes listed in WAC 173-303-9904 Specific Sources - Spent hydrotreating catalyst (EPA Hazardous Waste No. K171), and Spent hydrorefining catalyst (EPA Hazardous Waste No. K172). These wastes are not excluded if they exhibit one or more of the dangerous waste characteristics or criteria.

(kk) Leachate or gas condensate collected from landfills where certain solid wastes have been disposed: Provided, That:

(i) The solid wastes disposed would meet one or more of the listing descriptions for Hazardous Waste Codes K169, K170, K171, K172, K174, K175, K176, K177, and K178 if these wastes had been generated after the effective date of the listing;

(ii) The solid wastes described in (kk)(i) of this subsection were disposed prior to the effective date of the listing;

(iii) The leachate or gas condensate does not exhibit any characteristic or criteria of dangerous waste nor is derived from any other listed hazardous waste;

(iv) Discharge of the leachate or gas condensate, including leachate or gas condensate transferred from the landfill to a POTW by truck, rail, or dedicated pipe, is subject to regulation under sections 307(b) or 402 of the Clean Water Act.

(v) As of February 13, 2001, leachate or gas condensate derived from K169 - K172 is no longer exempt if it is stored or managed in a surface impoundment prior to discharge. After November 21, 2003, leachate or gas condensate derived from K176,

K177, and K178 will no longer be exempt if it is stored or managed in a surface impoundment prior to discharge. There is one exception: If the surface impoundment is used to temporarily store leachate or gas condensate in response to an emergency situation (for example, shutdown of wastewater treatment system): Provided, That the impoundment has a double liner, and: Provided further, That the leachate or gas condensate is removed from the impoundment and continues to be managed in compliance with the conditions of this paragraph after the emergency ends.

(ll) Dredged material. Dredged material as defined in 40 CFR 232.2 that is subject to:

(i) The requirements of a permit that has been issued by the U.S. Army Corps of Engineers or an approved state under section 404 of the Federal Water Pollution Control Act (33 U.S.C. 1344);

(ii) The requirements of a permit that has been issued by the U.S. Army Corps of Engineers under section 103 of the Marine Protection, Research, and Sanctuaries Act of 1972 (33 U.S.C. 1413); or

(iii) In the case of a U.S. Army Corps of Engineers civil works project, the administrative equivalent of the permits referred to in (ll) (i) and (ii) of this subsection, as provided for in U.S. Army Corps of Engineers regulations, including, for example, 33 CFR 336.1, 336.2 and 337.3.

(mm) Condensates derived from the overhead gases from kraft mill steam strippers that are used to comply with 40 CFR 63.446(e). The exemption applies only to combustion at the mill generating the condensates.

(nn) (i) Controlled substances, legend drugs, and over-the-counter drugs that are state-only dangerous wastes.

(A) Controlled substances as defined and regulated by chapter 69.50 RCW (Schedule I through V);

(B) Legend drugs as defined and regulated by chapter 69.41 RCW; and

(C) Over-the-counter drugs as defined and regulated by chapter 69.60 RCW.

(ii) Controlled substances, legend drugs, and over-the-counter drugs that are held in the custody of law enforcement agencies or possessed by any licensee as defined and regulated by chapter 69.50 RCW or Title 18 RCW and authorized to possess drugs within the state of Washington are excluded, provided the drugs are disposed of by incineration in a controlled combustion unit with a heat input rate greater than 250 million British thermal units/hour, a combustion zone temperature greater than 1500 degrees Fahrenheit, or a facility permitted to incinerate municipal solid waste.

(iii) For the purposes of this exclusion the term "drugs" means:

(A) Articles recognized in the official United States pharmacopoeia or the official homeopathic pharmacopoeia of the United States;

(B) Substances intended for use in the diagnosis, cure, mitigation, treatment, or prevention of disease in man or other animals; or

(C) Substances (other than food) intended to affect the structure or any function of the body of man or other animals, as defined in RCW 18.64.011(3). (Note: RCW 18.64.011 (3)(d) is intentionally not included in the definition of drugs for this exclusion.)

(iv) When possessed by any licensee the term drugs used in this exclusion means finished drug products.

(oo) (~~Reserve.~~) Cathode ray tubes (CRTs) and glass removed from CRTs:

(i) Prior to processing: These materials are not solid wastes if they are destined for recycling and if they meet the following requirements:

(A) Storage. CRTs must be either:

(I) Stored in a building with a roof, floor, and walls; or

(II) Placed in a container (that is, a package or a vehicle) that is constructed, filled, and closed to minimize releases to the environment of CRT glass (including fine solid materials).

(B) Labeling. Each container in which the CRT is contained must be labeled or marked clearly with one of the following phrases: "Used cathode ray tube(s) - contains leaded glass" or "leaded glass from televisions or computers." It must also be labeled: "Do not mix with other glass materials."

(C) Transportation. CRTs must be transported in a container meeting the requirements of (oo)(i)(A)(II) and (B) of this subsection.

(D) Speculative accumulation and use constituting disposal. CRTs are subject to the limitations on speculative accumulation as defined in WAC 173-303-016. If they are used in a manner constituting disposal, they must comply with the applicable requirements of WAC 173-303-505 instead of the requirements of this section.

(E) Exports. In addition to the applicable conditions specified in (oo)(i)(A) through (D) of this subsection, exporters of CRTs must comply with the following requirements:

(I) Notify EPA of an intended export before the CRTs are scheduled to leave the United States. A complete notification should be submitted sixty days before the initial shipment is intended to be shipped off-site. This notification may cover export activities extending over a twelve-month or lesser period. The notification must be in writing, signed by the exporter, and include the following information:

• Name, mailing address, telephone number and EPA/state ID number (if applicable) of the exporter of the CRTs.

• The estimated frequency or rate at which the CRTs are to be exported and the period of time over which they are to be exported.

• The estimated total quantity of CRTs specified in kilograms.

• All points of entry to and departure from each foreign country through which the CRTs will pass.

• A description of the means by which each shipment of the CRTs will be transported (for example, mode of transportation vehicle (air, highway, rail, water, etc.), type(s) of container (drums, boxes, tanks, etc.)).

● The name and address of the recycler and any alternate recycler.

● A description of the manner in which the CRTs will be recycled in the foreign country that will be receiving the CRTs.

● The name of any transit country through which the CRTs will be sent and a description of the approximate length of time the CRTs will remain in such country and the nature of their handling while there.

(II) Notifications submitted by mail should be sent to the following mailing address: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, 1200 Pennsylvania Ave., N.W., Washington, D.C. 20460. Hand-delivered notifications should be sent to: Office of Enforcement and Compliance Assurance, Office of Federal Activities, International Compliance Assurance Division, (Mail Code 2254A), Environmental Protection Agency, Ariel Rios Bldg., Room 6144, 1200 Pennsylvania Ave., N.W., Washington, D.C. In both cases, the following must be prominently displayed on the front of the envelope: "Attention: Notification of intent to export CRTs."

(III) Upon request by EPA, the exporter must furnish to EPA any additional information which a receiving country requests in order to respond to a notification.

(IV) EPA will provide a complete notification to the receiving country and any transit countries. A notification is complete when EPA receives a notification which EPA determines satisfies the requirements of (oo) (i) (E) (I) of this subsection. Where a claim of confidentiality is asserted with respect to any notification information required by (oo) (i) (E) (I) of this subsection, EPA may find the notification not complete until any such claim is resolved in accordance with 40 CFR 260.2.

(V) The export of CRTs is prohibited unless the receiving country consents to the intended export. When the receiving country consents in writing to the receipt of the CRTs, EPA will forward an acknowledgment of consent to export CRTs to the exporter. Where the receiving country objects to receipt of the CRTs or withdraws a prior consent, EPA will notify the exporter in writing. EPA will also notify the exporter of any responses from transit countries.

(VI) When the conditions specified on the original notification change, the exporter must provide EPA with a written renotification of the change, except for changes to the telephone number in (oo) (i) (E) (I) (first bullet) of this subsection and decreases in the quantity indicated pursuant to (oo) (i) (E) (I) (third bullet) of this subsection. The shipment cannot take place until consent of the receiving country to the changes has been obtained (except for changes to information about points of entry and departure and transit countries pursuant to (oo) (i) (E) (I) (fourth bullet) and (i) (E) (I) (eighth bullet) of this section) and the exporter of CRTs receives from EPA a copy of the acknowledgment of consent to export CRTs reflecting the receiving country's consent to the changes.

(VII) A copy of the acknowledgment of consent to export CRTs must accompany the shipment of CRTs. The shipment must conform to the terms of the acknowledgment.

(VIII) If a shipment of CRTs cannot be delivered for any reason to the recycler or the alternate recycler, the exporter of CRTs must renotify EPA of a change in the conditions of the original notification to allow shipment to a new recycler in accordance with (oo)(i)(E)(VI) of this subsection and obtain another acknowledgment of consent to export CRTs.

(IX) Exporters must keep copies of notifications and acknowledgments of consent to export CRTs for a period of five years following receipt of the acknowledgment.

(ii) Requirements for used CRT processing: CRTs undergoing CRT processing as defined in WAC 173-303-040 are not solid wastes if they meet the following requirements:

(A) Storage. CRTs undergoing processing are subject to the requirement of (oo)(i)(D) of this subsection.

(B) Processing.

(I) All activities specified in the second and third bullets of the definition of "CRT processing" in WAC 173-303-040 must be performed within a building with a roof, floor, and walls; and

(II) No activities may be performed that use temperatures high enough to volatilize lead from CRTs.

(iii) Processed CRT glass sent to CRT glass making or lead smelting: Glass from CRTs that is destined for recycling at a CRT glass manufacturer or a lead smelter after processing is not a solid waste unless it is speculatively accumulated as defined in WAC 173-303-016.

(iv) Use constituting disposal: Glass from used CRTs that is used in a manner constituting disposal must comply with the requirements of WAC 173-303-505.

(v) Notification and recordkeeping for cathode ray tubes (CRTs) exported for reuse.

(A) Persons who export CRTs for reuse must send a one-time notification to the U.S. EPA Regional Administrator. The notification must include a statement that the notifier plans to export CRTs for reuse, the notifier's name, address, and EPA/state ID number (if applicable) and the name and phone number of a contact person.

(B) Persons who export CRTs for reuse must keep copies of normal business records, such as contracts, demonstrating that each shipment of exported CRTs will be reused. This documentation must be retained for a period of at least five years from the date the CRTs were exported.

(pp) Zinc fertilizers made from hazardous wastes provided that:

(i) The fertilizers meet the following contaminant limits:

(A) For metal contaminants:

	Maximum Allowable Total Concentration Constituent in Fertilizer, per Unit (1%) of Zinc (ppm)
Arsenic	0.3
Cadmium	1.4

Chromium	0.6
Lead	2.8
Mercury	0.3

(B) For dioxin contaminants the fertilizer must contain no more than eight parts per trillion of dioxin, measured as toxic equivalent (TEQ).

(ii) The manufacturer performs sampling and analysis of the fertilizer product to determine compliance with the contaminant limits for metals no less than every six months, and for dioxins no less than every twelve months. Testing must also be performed whenever changes occur to manufacturing processes or ingredients that could significantly affect the amounts of contaminants in the fertilizer product. The manufacturer may use any reliable analytical method to demonstrate that no constituent of concern is present in the product at concentrations above the applicable limits. It is the responsibility of the manufacturer to ensure that the sampling and analysis are unbiased, precise, and representative of the product(s) introduced into commerce.

(iii) The manufacturer maintains for no less than three years records of all sampling and analyses performed for purposes of determining compliance with the requirements of (pp)(ii) of this subsection. Such records must at a minimum include:

(A) The dates and times product samples were taken, and the dates the samples were analyzed;

(B) The names and qualifications of the person(s) taking the samples;

(C) A description of the methods and equipment used to take the samples;

(D) The name and address of the laboratory facility at which analyses of the samples were performed;

(E) A description of the analytical methods used, including any cleanup and sample preparation methods; and

(F) All laboratory analytical results used to determine compliance with the contaminant limits specified in this subsection (3) (pp).

(qq) Debris. Provided the debris does not exhibit a characteristic identified in WAC 173-303-090, the following materials are not subject to regulation under this chapter:

(i) Hazardous debris that has been treated using one of the required extraction or destruction technologies specified in Table 1 of 40 CFR section 268.45, which is incorporated by reference at WAC 173-303-140 (2)(a); persons claiming this exclusion in an enforcement action will have the burden of proving by clear and convincing evidence that the material meets all of the exclusion requirements; or

(ii) Debris that the department, considering the extent of contamination, has determined is no longer contaminated with hazardous waste.