



- Notes:**
1. Within 100 feet of river, backfill area of soil removal with 0.5 foot of sand (>50% finer than U.S. No. 10 sieve and <5% finer than U.S. No. 200 sieve). Cover sand with 1.0 foot, minimum, layer of 2-inch or greater gravel and cobble mixture or alternative material approved by the Engineer. Where side slopes are 1.5H:1V or steeper, place gravel and cobble mixture before placing sand to maintain stable slope conditions.
 2. Within 100 feet of river, where side slope soils are disturbed, backfill with sufficient topsoil to fill voids between large particles to aid revegetation of habitat near river.
 3. No backfilling required. Hydroseed with native plant mix and appropriate mulch/tackifier.
 4. Backfill with 1.5 feet, minimum, layer of 2-inch or greater gravel and cobble mixture approved by the Engineer.
 5. All areas of excavation below ordinary high water may be backfilled with 4-inch-diameter or greater gravel extending at least 1.5 feet below adjacent grades for additional erosion protection.
 6. Revegetation shall be performed in accordance with restoration plans prepared by a habitat and restoration professional and submitted with the construction drawings.



- MW-15 Monitoring Well Location and Number
- WW-EW-3 Extraction Well Location and Number
- T Horizontal Trench Access Point
- Assumed Excavation Limits of PCB-Impacted Soil
- Assumed Excavation Limits of Clean Soil

Approximate Cross Section Location and Designation



Kaiser West Discharge Ravine Spokane Valley, Washington	
WDR Backfill and Grading Plan	
2644-105	4/07
	Figure
	2-5

EAL 05/21/07 2644105-009.dwg