

From: [Mark Buehrer](#)
To: [ECY RE WW SW Manual Comments](#)
Cc: [Wulkan, Bruce \(PSP\)](#); ["Curtis Hinman"](#); [Colleen Mitchell](#)
Subject: 2012 Draft Stormwater Manual - LID Feasibility
Date: Friday, February 03, 2012 5:13:01 PM
Attachments: [image003.png](#)

2020 has designed more than 200 LID features over the past 12 years. We have found ways to use LID methods on almost all of our projects.

More than half of our LID features have been on clayey soils with no or little infiltration. Sometimes we need to place a liner under the LID feature.

I am not clear on all of the proposed criteria, but from what I have heard, there appears to be many ways a site does not need to use LID.

I think the proposed LID Feasibility criteria needs to be re-evaluated so that LID uses are truly promoted for use on all projects. And, since LID is more cost-effective and better for the environment, why wouldn't we want LID on all projects? It's a win-win scenario!

.....
Mark S. Buehrer, PE, Director
2020 ENGINEERING
www.2020engineering.com
Wellspring Building
814 Dupont Street
Bellingham, WA 98225
Ph: (360) 671-2020, Ext. 103



Become a fan of 2020 ENGINEERING, a proud sponsor of Cascadia Green Building Council



"To provide simple economic solutions to complex environmental issues...to meet future needs."

.....
Mark S. Buehrer, PE, Director
2020 ENGINEERING
www.2020engineering.com
Wellspring Building
814 Dupont Street
Bellingham, WA 98225
Ph: (360) 671-2020, Ext. 103



Become a fan of 2020 ENGINEERING, a proud sponsor of Cascadia Green Building Council



"To provide simple economic solutions to complex environmental issues...to meet future needs."